TermoPasty®

TECHNICAL DATA SHEET

Vaseline oil

A versatile product that combines effective lubrication with reliable protection against corrosion and moisture. Thanks to its properties, it is ideal for use in both precision mechanics and industry. Its neutrality towards plastics and rubber allows for broad application across various industries.

Product features:

- protection against moisture and corrosion,
- reduces friction, eliminates squeaks and creaks,
- neutral towards plastics and rubber,
- easy application and even distribution,
- excellent lubricating and anti-stick properties.

Applications:

- machine and equipment components,
- delicate precision mechanisms,
- lubrication of window and door fittings,
- processes involving extrusion and vacuum forming.

Physicochemical properties	
Appearance	Colorless gas / liquid
Density at 20°C	~0.86 g/cm^3
Viscosity at 40°C (liquid)	~70 cSt
Kinematic viscosity at 40°C (aerosol)	~70 mm^2/s
Operating temperature	-10°C to 90°C
Shelf life	3 years

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

Creation date: 2nd July 2025 | Revision date: 2nd December 2025 | Version: 1.1

Compatibility:

Vaseline oil is neutral towards most materials, including metals, plastics, and rubber. Thanks to this, it can be safely used in delicate mechanisms, industrial processes, and for the protection of elements exposed to moisture and corrosion.

Application method	
Applicator	Yes
Aerosol with tube	Yes
Bottle/Canister	Yes
Brush	Yes
Immersion	Yes

Usage instructions:

Restricted to professional users. Read safety data sheet carefully prior to use.

Regardless of whether you choose the liquid, aerosol, or other form, ensure the surface is dry and clean. For the liquid version, apply the oil directly to the selected area or use a brush or cloth for even distribution. For the aerosol version, use the included tube for precise application and spray the surface. Allow the oil to absorb before use to achieve maximum effectiveness.

Package	
Bottle with applicator	50 ml (ART.AGT-017) - 12 pcs.* 100 ml (ART.AGT-018) - 12 pcs.*
Aerosol	300 ml (ART.AGT-019) - 12 pcs.*
Bottle/Canister	1 l (ART.AGT-099) - 1/4 pcs.* 5 l (ART.AGT-245) - 1 pc.*

*Quantity of pcs. in a bulk package

Storage:

Store in tightly closed containers in a cool, dry place, away from heat sources and direct sunlight. Store at a temperature of 0-50°C. Do not store with oxidizing substances. Do not use PCW packaging.

Technical support:

AG TermoPasty provides technical support, answering questions about the technical specifications and applications of our products. Please contact us via email at info@termopasty.pl.

Note:

The data presented in this document reflect our current state of knowledge and describe the typical properties and applications of the product. However, the responsibility for determining the suitability of this product for specific applications lies with the user. AG TermoPasty is not liable for the results of the product's use, as the conditions of its application are beyond our control.