NOTIFIER® by Honeywell

Analogue call point

M5A - W5A series is an indoor analogue break-glass call point designed to be use as manual alarm for fire system. Two models available: M5A-xx e W5A.-xx series include an addressable mini-module for interfacing with NOTIFIER control panels. All call points are compliant to the EU directive for CE mark and CPR certified for EN54.11 and EN54.18.



> *MAIN FEATURES*

- Easy to install
- Status LED; it show the different device state:
- BLINKING, in communication with control panel
- STAEDY, alarm
- Easy wiring thanks plug-in connectors
- Easy test; introducing the supplied specific key, the
- glass will move down, switching manual call point in
- alarm condition.
- Braking-glass with protective label or flexible
- resettable membrane.
- Suitable for wall mounting or flush mounting. The
- base is supplied with call point.

> *Application*

Call series is suitable for commercial, industrial or residential application. The series is used as manual call point in case of fire. It is usually installed outside doors so that it can be used in evacuation event

> *Installation*

A suitable plastic box (supplied) can be used for mounting. Used for both sight and recessed installations. The base is already supplied with the button, for mounting on box B503, a special adapter is available.

> *Function*

If the glass is break, the internal micro-switch will be
activated and the alarm signal will transmit to panel.

SERIES



M5A-RP02SG-N026-01

Addressable break-glass call point indoor IP24D.



W5A-RP02SG-N026-01

Addressable break-glass call point outdoor IP67.

Tutti i dati sono soggetti a cambiamento senza preavviso. Tutti i diritti di questa pubblicazione sono riservati.
Per maggiori informazioni contattare:
Notifier Italia S.r.l.
Via Grandi, 22 20097 San Donato Milanese (MI)
Tel.: 02-51897.1 Fax: 02-51897.30 E-Mail: notifier@notifier.it
www.notifier.it

SISTEMA GESTIONE QUALITÀ E AMBIENTE CERTIFICATI
UNI EN ISO 9001:2008 - UNI EN ISO 14001:2004

FEATURES

Electrical

- Operating voltage: 15-30Vcc
- Main voltage: 24Vcc

Absorption

Stand-by: 350μA, 660μA With communication

- In Alarm: 6mA (Typical)
- Red LED: 2mA (tipico)
- Yellow LED: 7.5mA max (tipico)

Enviromental

- IP grade:
  - M5A: IP24D
  - W5A IP67
- Operative Temperature:
  - M5A: -10° a +55°C
  - W5A-30°+70°C

Technical

- Section cable: 0,5 – 2,5mm2
- Weight:
  - -M5A: 110 gr./ 160gr. with base
  - -W5A 270gr.
- Dimension:
  - M5A 89 x93x59,5 (with base)
  - W5A: 97,5 x93x65,5 (with base)

accessories



SUS758

Box of 10 pieces of spare glasses for Series call points. Neutral inscription.



PS200

Plastic cover for manual call points.



M700K-503

Frame and adapter for B503 wall boxes. Pack of 10 pcs.



SR1T

Red mounting support.

NOTIFIER® by Honeywell

Via Grandi, 22
20097
San Donato Milanese (MI)

T: 02 51 897 1
F: 02 51 897 30
E: notifier@notifier.it
www.notifier.it