tesa® PRO 74613 Duct Tape

Product Information

Professional Repairing tape - best allround helper with long-lasting bonding power

Product Description

The new tesa PRO Duct Tape 74613 will help you satisfy your customers. Due to its reliable bonding power and adaptability, your repair will be quick, clean and long-lasting. No matter whether you need to fixate cables during a painting job or seal a broken pipe, our PRO Duct Tape is suitable for most surfaces. The utility grade duct tape is based on synthetic rubber with a PET-fabric. The perfect addition for your craftsmen toolbox, easy to tear and always ready to go!

Product Features

- Your best helper for all repairs and fixations: Quick to apply and easy to tear by hand, tesa PRO Duct Tape can be used both outdoors and indoors.
- tesa PRO Duct Tape is water repellent and works even on slighlty rough surfaces. No matter the application, this tape fulfills the needs of every craftsmen.
- Due to its design, the tesa PRO Duct Tape is easy to unwind and adapts to every product to ensure clean sealing. Making your life easier, bond by bond!
- This general purpose tape can be used for various applications such as repairing, marking, fastening, sealing and packaging.

Application Fields

- This Duct Tape works best on clean, smooth surfaces
- Apply the tape and press firmly onto the surface

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing material	PE-film with PET-filament
Type of adhesive	synthetic rubber
Total thickness	175 µm

Product Assortment

Available colors	black, grey

For latest information on this product please visit http://l.tesa.com/?mp=74613

tesa® PRO 74613 Duct Tape

Product Information

Properties/Performance Values

Abrasion resistance	good	Oil and grease resistance	no
Temperature resistance	medium	Residue free removal	no
Elongation at break	14 %	Salt water resistance	medium
Tensile strength	40 N/cm	Solvent free	yes
Adhesive strength	High adhesion	Tear resistance	yes
Ageing resistance (UV)	medium	Tensibility	14 %
Chemical resistance	medium	Water resistance	low
Hand tearability	good	Waterproof	yes
Humidity resistance	medium	Writable	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?mp=74613