Reolink

Go Series G430

2K 4MP 4G Pan-Tilt Camera, Battery or Solar Powered, with Person/Vehicle Detection

- 4G LTE Network
- 2K 4MP Super HD
- Person/Vehicle Detection



Specifications

Video & Audio	
Image Sensor	1/2.7" CMOS sensor
Video Resolution	2880 x 1660 (5 megapixels) @15fps
Lens	f=4mm, F1.6
Video Compression	H.265
Field of View	Horizontal: 90° Vertical: 47° Diagonal: 110°
Infrared Night Vision	Up to 10 meters (33ft) ; LED: 2pcs/1.2W/850nm (Auto-switching with IR-cut filter)
Color Night Vision	2pcs/2.4W/6500K
Audio	two-way audio
Power	
Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
Solar	Reolink Solar Panel
Interface	

Power Port	USB Type-C port
Reset Button	Built-in microphone and speaker
Audio In/Out	Supports Max.128GB microSD card (32GB included)
Storage	
microSD Card Slot	YES
Pan & Tilt	
PT Angle(Max.)	Pan: 355°; tilt: 140°
Preset Points	Supports 1 guard position & up to 32 preset positions
3G/4G Bandwidth	
Frequency Bands	• Europe Version: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 • U.S. Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 • Australia Version: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8
Software	
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)
Other Features	
Smart Alarm	PIR detection/person detection/vehicle detection/ animal detection
PIR Detecting Distance	Adjustable up to 10m (33 ft)
PIR Detecting Angle	120° horizontal
Recording Modes	Triggered recording
Time Lapse	YES
Smart Home Compatibility	Google Assistant, Alexa
Cloud Storage	Supports Reolink Cloud (available in selected countries)
Working Environment	

Operating Temperature	-10 to 55° C (14° to 131° F)
Weather Resistance	IP64
Mechanical	
Size	Φ98 x 112mm (Φ3.7 x 4.4 in)
Weight Battery Included	485 g (17.1 oz)
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/