tesa® PRO 66958 Mounting Universal

Product Information

Strong and double-sided tape - Ideal for indoor use - Simple solution for fixing lighter objects - Hand tearable

Product Description

tesa PRO Mounting Universal is a must-have, multi purpose tape for every professional craftsman or -woman working in indoor spaces. Fix light objects such as cable channels, stucco mounting and skirting, secure and permanently on most surfaces without leaving holes or damages in the wall structure. tesa PRO Mounting Universal is a true all-rounder! The smart solution for a quick and easy assignment. Apply in vertical strips and along the full length of the object or surface. Press firmly for five seconds on dirt- and dust-free surface.

Product Features

- Durable and resistant: Long-term temperature resistance at 40 degrees and short-term resistance at 60 degrees
- Reliable hold without damaging the wall structure: tesa PRO Mounting Universal doesn't require the use of screws, plugs or nails - for fast and easy mounting with no tools necessary
- Ideal for interior use: Strong double-sided adhesive tape for secure fixing of lighter objects such as cable channels, stucco mounting and skirting - compensates slightly rough surfaces
- Easy to use: The mounting tape can be cut into individual small or large pieces for an adhesive strip in the optimized size

Application Fields

Easy to apply:

- In order for the mounting tape to develop its full holding power, the object and surface must be free of dust, dirt and grease.
- Don't touch the open adhesive surface as it could impair the adhesive strength.
- Apply in vertical strips and along the full length of the object or surface.
- Press firmly for five seconds.
- For removal, carefully pull the mounting tape parallel from the wall. As the mounting tapes are intended for permanent use, material residues may remain on the object. Try to remove with tesa adhesive remover.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?mp=66958