

DH-SD3D416NB-GNY

4M 16x IR WizSense Network PTZ Camera



WizSense

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

Series Overview

With its powerful optical zoom and accurate pan, tilt, and zoom functions, the SD3D series camera provides an all-in-one solution for long distance video surveillance in outdoor settings. Their small and compact design make them easy to install. They are also compatible with IR illuminators, making them great for use in dark and low-light conditions.

Functions

Starlight Technology

Dahua Starlight technology utilizes advanced image processing and optical technologies to deliver clear videos, even in low-lighting environments. This technology is extensively employed across a range of settings that have inadequate lighting.


SMD 3.0

Empowered by deep-learning algorithms, Dahua SMD filters out motion detection alarms triggered by targets that are not a concern. It quickly recognizes humans and vehicles, triggering alarms when an intrusion occurs.

Protection (IP66, TVS 6000 V)

IP66, TVS 6000 V lightning proof, surge protection, and voltage transient protection.

- 1/2.8" 4Megapixel CMOS
- 16x optical zoom Starlight technology
- Max. 25/30 fps@4MP
- IR distance up to 80 m
- IVS(Human/Vehicle Detection)
- SMD 3.0
- IP66
- Smart Light +
- Preset Patrol



IVS

With advanced video algorithm, Dahua IVS technology supports intelligent functions, such as tripwire and intrusion.

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Smart Light+

Equipped with advanced LEDs and beam processing technology, the camera effectively reduces interference of stray light, ensuring concentrated illumination within the lens's field of view. This allows the camera to easily produce clear images that reveal the fine details of targets even in low light conditions.

Wide Dynamic Range

The camera produces vivid images, even in high-contrast lighting conditions, by using industry-leading wide dynamic range (WDR) technology. For scenes that quickly alternate between bright and low lighting, WDR adjusts to fully capture both the bright and dark areas of a scene, producing superior quality videos.

Technical Specification

Camera

Image Sensor	1/2.8" CMOS
Pixel	4 MP
Max. Resolution	2560 (H) × 1440 (V)
ROM	128 MB
RAM	128 MB
Electronic Shutter Speed	1 s–1/30,000 s
Scanning System	Progressive
Min. Illumination	Color: 0.005 lux@F1.6; Black and white: 0.0005 lux@F1.6; 0 lux (IR light on)
Illumination Distance	80 m (262.47 ft) (IR)
Illuminator On/Off Control	Zoom Prio; Manual; Auto; Off
Illuminator Number	3 (IR)

Lens

Focal Length	5.0 mm–80 mm				
Max. Aperture	F1.6–F3.5				
Field of View	H: 50.56°–3.84°; V: 29.48°–2.16°; D: 57.69°–4.39°				
Optical Zoom	16×				
Focus Control	Auto; Semi-auto; Manual				
Close Focus Distance	0.1 m–1 m (0.33 ft–3.28 ft)				
Iris Control	Auto; Manual; Iris prio				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	5.0 mm–80 mm	1,600.00 m (5,249.3 4 ft)	632.00 m (2,073.4 9 ft)	320.00 m (1,049.8 7 ft)	160.00 m (524.93 ft)
	*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool.				

PTZ

Pan/Tilt Range	Pan: 0° to 360° endless; Tilt: –15° to +90°, auto flip 180°
Manual Control Speed	Pan: 0.1°–40°/s; Tilt: 0.1°–40°/s
Preset Speed	Pan: 0.1°–40°/s; Tilt: 0.1°–40°/s
Preset	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Power-off Memory	Yes
Idle Motion	Preset

PTZ Protocol	DH-SD
--------------	-------

Smart Event

IVS	Tripwire; intrusion
-----	---------------------

Intelligence

SMD	SMD 3.0
-----	---------

Video

Video Compression	Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub Stream 1)
Streaming Capability	2 streams
Resolution	4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Video Frame Rate	Main stream: 4M/3M/1080p/1.3M/720p@ (1–25/30 fps) Sub stream: D1/VGA/CIF@ (1–25/30 fps)
Bit Rate Control	CBR/VBR
Video Bit Rate	H264: 96–8,192 kbps H265: 38–8,192 kbps
Day/Night	Auto (ICR); Color/B/W
BLC	Yes
WDR	120 dB
HLC	Yes
White Balance	Auto; indoor; outdoor; ATW; manual; sodium lamp; natural light; street lamp
Gain Control	Auto; manual
Noise Reduction	2D NR; 3D NR
Motion Detection	Yes
Region of Interest (RoI)	Yes
Defog	Electronic Image Stabilization (EIS)
Digital Zoom	5×
Image Rotation	180°
S/N Ratio	≥55 dB

Network

Network Port	RJ-45 (10/100 Base-T)
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; SSL; FTP; ARP; RTCP; RTP; IP Filter; RTMP
Interoperability	CGI; SDK; ONVIF (Profile S & Profile T)
Streaming Method	Unicast/Multicast
User/Host	20 (total bandwidth: 64 M)
Storage	Micro SD card (256 GB); FTP
Browser	IE 7 and later versions; All Chrome versions; All Firefox versions; All Safari versions
Management Software	DSS Pro

Mobile Client	iOS;Android
Certification	
Certifications	CE: EN55032/EN55024/EN50130-4
Port	
Alarm Linkage	Capture; recording; send email
Alarm Event	Motion/tampering detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection
Power	
Power Supply	12 VDC, 2 A $\pm$ 10% PoE+ (802.3at)
Power Consumption	Basic: 8 W Max. (Basic power consumption + WDR + intelligence on + IR on + PTZ operation + Heater): 18 W (12 VDC)
Power Adapter	Optional
Environment	
Operating Temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Operating Humidity	$\leq$ 95%
Protection	IP66;TVS 6000 V lightning proof; surge protection; voltage transient protection
Structure	
Product Dimensions	240 mm $\times$ Φ 151.5 mm (9.45" $\times$ Φ 5.94")
Net Weight	1.5 kg (3.31 lb)
Gross Weight	2.5 kg (5.51 lb)
Filter	
Remarks	The precision of the presets for PTZ cameras might vary depending on different series. For scenes with high requirements on the precision, contact your local sales representative for assistance with selecting the model.

Ordering Information

Type	Model	Description
Network PTZ Camera	DH-SD3D416NB-GNY	4M 16x IR WizSense Network PTZ Camera
Accessories	PFB5310W	Wall Mount Bracket
	DH-PFB300C	Ceiling Mount Bracket
	PFA7711	Mount Adapter
	DH-PFA150	Pole Mount Bracket
	DH-PFA156	Pole Mount Bracket
	DH-PFA121	Water-proof Junction Box

Accessories

Included:



PFB5310W
Wall Mount Bracket

Optional:



DH-PFA121
Water-proof Junction Box



DH-PFA150
Pole Mount Bracket




DH-PFA156
Pole Mount Bracket



DH-PFB300C
Ceiling Mount Bracket



PFA7711
Mount Adapter



Dimensions (mm[inch])

