

OVERVIEW



|                                  |                                              |
|----------------------------------|----------------------------------------------|
| 1. Smart card reader *           | 6. 2x Thunderbolt 4                          |
| 2. Nano-SIM card slot *          | 7. HDMI                                      |
| 3. USB-A (USB 5Gbps)             | 8. USB-A (USB 5Gbps), Always On              |
| 4. Ethernet (RJ-45)              | 9. Headphone / microphone combo jack (3.5mm) |
| 5. Kensington Nano Security Slot |                                              |

- Notes:
- Items with \* are only available on selected models

PERFORMANCE

Processor

Processor Family

Intel® U or H Series Core Ultra 5 / 7 Processor (Series 1)

Processor\*\*

| Processor Name    | Cores                                  | Threads | Base Frequency                                   | Max Frequency                                    | Cache                   | Processor Graphics                                 | NPU                            |
|-------------------|----------------------------------------|---------|--------------------------------------------------|--------------------------------------------------|-------------------------|----------------------------------------------------|--------------------------------|
| Core Ultra 5 125H | 14 (4 P-core + 8 E-core + 2 LP E-core) | 18      | P-core 1.2GHz / E-core 700MHz / LP E-core 700MHz | P-core 4.5GHz / E-core 3.6GHz / LP E-core 2.5GHz | 18MB Intel® Smart Cache | Intel® Arc™ Graphics, up to 18 TOPS <sup>[1]</sup> | Intel® AI Boost, up to 11 TOPS |
| Core Ultra 5 125U | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 1.3GHz / E-core 800MHz / LP E-core 700MHz | P-core 4.3GHz / E-core 3.6GHz / LP E-core 2.1GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 7 TOPS                      | Intel® AI Boost, up to 11 TOPS |
| Core Ultra 5 135H | 14 (4 P-core + 8 E-core + 2 LP E-core) | 18      | P-core 1.7GHz / E-core 1.2GHz / LP E-core 700MHz | P-core 4.6GHz / E-core 3.6GHz / LP E-core 2.5GHz | 18MB Intel® Smart Cache | Intel® Arc™ Graphics, up to 18 TOPS <sup>[2]</sup> | Intel® AI Boost, up to 11 TOPS |
| Core Ultra 5 135U | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 1.6GHz / E-core 1.1GHz / LP E-core 700MHz | P-core 4.4GHz / E-core 3.6GHz / LP E-core 2.1GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS                      | Intel® AI Boost, up to 11 TOPS |
| Core Ultra 7 155H | 16 (6 P-core + 8 E-core + 2 LP E-core) | 22      | P-core 1.4GHz / E-core 900MHz / LP E-core 700MHz | P-core 4.8GHz / E-core 3.8GHz / LP E-core 2.5GHz | 24MB Intel® Smart Cache | Intel® Arc™ Graphics, up to 18 TOPS <sup>[3]</sup> | Intel® AI Boost, up to 11 TOPS |
| Core Ultra 7 155U | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 1.7GHz / E-core 1.2GHz / LP E-core 700MHz | P-core 4.8GHz / E-core 3.8GHz / LP E-core 2.1GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS                      | Intel® AI Boost, up to 11 TOPS |
| Core Ultra 7 165H | 16 (6 P-core + 8 E-core + 2 LP E-core) | 22      | P-core 1.4GHz / E-core 900MHz / LP E-core 700MHz | P-core 5.0GHz / E-core 3.8GHz / LP E-core 2.5GHz | 24MB Intel® Smart Cache | Intel® Arc™ Graphics, up to 19 TOPS <sup>[4]</sup> | Intel® AI Boost, up to 11 TOPS |
| Core Ultra 7 165U | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 1.7GHz / E-core 1.2GHz / LP E-core 700MHz | P-core 4.9GHz / E-core 3.8GHz / LP E-core 2.1GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS                      | Intel® AI Boost, up to 12 TOPS |

Notes:

[1], [2], [3], [4] Intel® Arc™ graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

AI (Artificial Intelligence)

AI PC Category

AI PC<sup>[1]</sup>

NPU

Integrated Intel® AI Boost, up to 11 TOPS

Notes:

[1] AI PCs have a NPU capable of 10+ TOPs to run the Copilot assistant by pressing the optional Microsoft® Copilot key or using Win + C.

Operating System

Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64<sup>[1]</sup>
- Fedora Linux<sup>[2]</sup>
- Ubuntu Linux<sup>[3]</sup>
- Linux<sup>[4]</sup>
- No preload operating system

Notes:

[1] Windows® 11 DG Windows® 10 Pro 64 is for special bid only.  
[2], [3], [4] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics\*\*

| Graphics                            | Type       | Memory | Key Features  |
|-------------------------------------|------------|--------|---------------|
| Intel® Graphics                     | Integrated | Shared | DirectX® 12.1 |
| Intel® Arc™ Graphics <sup>[1]</sup> | Integrated | Shared | DirectX® 12.2 |

Notes:

[1] Intel® Arc™ graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

Monitor Support

Monitor Support<sup>[1]</sup>

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and Thunderbolt™)

- HDMI® supports up to 4K@60Hz
- Thunderbolt™ supports up to 8K@60Hz<sup>[2]</sup>

Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.  
[2] 8K resolution support needs 2 display pipes. That is, simultaneous display number will “-1” when 8K resolution displayed.

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory<sup>[1]</sup>

Up to 64GB DDR5-5600

Memory Slots

Two DDR5 SODIMM slots, dual-channel capable

Memory Type

DDR5-5600

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Max Storage Support<sup>[1]</sup>

One drive, up to 2TB M.2 2280 SSD

Storage Slot<sup>[2]</sup>

One M.2 2280 PCIe® 4.0 x4 slot

Storage Type\*\*

| Disk Type    | Interface                             | Offering            | Security |
|--------------|---------------------------------------|---------------------|----------|
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 4.0 x4             | 256GB / 512GB / 1TB | Opal 2.0 |
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 4.0 x4 Performance | 512GB / 1TB / 2TB   | Opal 2.0 |

Notes:

- [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
- [2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.
- PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);
- PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);
- PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby Audio™

Microphone

- Dual-microphone array, 360° far-field, Dolby Voice®
- No microphone

Camera\*\*

- 5.0MP + IR discrete, with privacy shutter, fixed focus, temporal noise reduction
- 5.0MP, with privacy shutter, fixed focus, temporal noise reduction
- No camera<sup>[1]</sup>

Notes:

- [1] No camera is for special bid only.

Battery

Battery\*\*<sup>[1]</sup>

- 39.3Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter<sup>[2]</sup>
- 52.5Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Battery Life<sup>[3]</sup>

Configuration 1 (max battery life)  
MobileMark® 25: up to 11.5 hr with 600 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 10.7 hr / 24.8 hr @200nits  
Local video playback: up to 20.7 hr @150nits

Alternate configuration 2  
MobileMark® 25: up to 11.2 hr with 666 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 10.9 hr / 24.1 hr @200nits  
Local video playback: up to 20.0 hr @150nits

Alternate configuration 3  
MobileMark® 25: up to 10.5 hr with 637 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 8.9 hr / 19.8 hr @200nits  
Local video playback: up to 18.1 hr @150nits

Notes:

- [1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.

[2] 39.3Wh battery is for special bid only.

[3] Configuration 1 (max battery life): WUXGA low power (non-touch), Intel® Core™ Ultra 5 125U, 8GB DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA low power (non-touch), Intel® Core™ Ultra 5 125H, 8GB DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

Alternate configuration 3: WUXGA (non-touch), Intel® Core™ Ultra 5 135U, 16GB DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using [MobileMark® 25](#), JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to [Microsoft® link](#) for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter\*\*[1]

- 45W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter[2]

Notes:

[1] AC adapter offerings depend on the country.

[2] No power adapter is for special bid only.

DESIGN

Display

Display\*\*[1]

| Size | Resolution        | Touch       | Type   | Brightness | Surface                                  | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features                                                      |
|------|-------------------|-------------|--------|------------|------------------------------------------|--------------|----------------|-------------|--------------|-------------------------|-------------------------------------------------------------------|
| 14"  | WUXGA (1920x1200) | Non-touch   | IPS[2] | 400nits    | Anti-glare                               | 16:10        | 1000:1         | 45% NTSC    | 60Hz         | 89° / 89° / 89° / 89°   | 3M™ DBEF5                                                         |
| 14"  | WUXGA (1920x1200) | Multi-touch | IPS[3] | 400nits    | Anti-glare                               | 16:10        | 1000:1         | 45% NTSC    | 60Hz         | 89° / 89° / 89° / 89°   | Eyesafe® Certified 2.0, 3M™ DBEF5                                 |
| 14"  | WUXGA (1920x1200) | Non-touch   | IPS[4] | 400nits    | Anti-glare                               | 16:10        | 1000:1         | 100% sRGB   | 60Hz         | 85° / 85° / 85° / 85°   | Low power, Eyesafe® Certified 2.0                                 |
| 14"  | WUXGA (1920x1200) | Multi-touch | IPS[5] | 500nits    | Anti-glare                               | 16:10        | 1500:1         | 100% sRGB   | 60Hz         | 89° / 89° / 89° / 89°   | ThinkPad® Privacy Guard                                           |
| 14"  | 2.2K (2240x1400)  | Non-touch   | IPS[6] | 300nits    | Anti-glare                               | 16:10        | 1500:1         | 100% sRGB   | 60Hz         | 85° / 85° / 85° / 85°   | TÜV Rheinland® Low Blue Light (Hardware Solution)                 |
| 14"  | 2.8K (2880x1800)  | Non-touch   | OLED   | 400nits    | Anti-glare, anti-reflection, anti-smudge | 16:10        | 100,000:1      | 100% DCI-P3 | 120Hz        | 85° / 85° / 85° / 85°   | DisplayHDR™ True Black 500, Dolby Vision®, Eyesafe® Certified 2.0 |

Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Screen-to-Body Ratio

85.73%

Notes:

[1] 3M™ DBEF5 (Dual Brightness Enhancement Film) improves the experience with higher brightness and lower energy.  
[2], [3], [4], [5], [6] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, key travel 1.5mm / 1.35mm (Fn row & G/H/B), Copilot key

Keyboard Backlight

- LED backlight
- Non-backlight

UltraNav™

TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu  
Glass-like Mylar® surface multi-touch 3-button Trackpad, 60 x 115 mm (2.36 x 4.53 inches)

Mechanical

Dimensions (WxDxH)<sup>[1]</sup>

315.9 x 223.7 x 17.7 mm (12.44 x 8.81 x 0.7 inches)

Weight<sup>[2]</sup>

| Models                                     | Weight                         |
|--------------------------------------------|--------------------------------|
| Models with black cover and 39.3Wh battery | Starting at 1.31 kg (2.89 lbs) |
| Models with grey cover and 39.3Wh battery  | Starting at 1.36 kg (2.99 lbs) |
| Models with black cover and 52.5Wh battery | Starting at 1.38 kg (3.05 lbs) |
| Models with grey cover and 52.5Wh battery  | Starting at 1.43 kg (3.15 lbs) |

Case Color\*\*

- Black
- Grey

Case Material\*\*

- Models with black cover: PC + 20% CF (top), PC + 20% CF (bottom)
- Models with grey cover: aluminium (top), PC + 20% CF (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.  
[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®\*\*<sup>[1]</sup>

- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, Intel® vPro® technology support<sup>[2]</sup>
- Intel® Wi-Fi® 7 BE200, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.3 (Bluetooth® 5.4 hardware ready), Intel® vPro® technology support<sup>[3]</sup>

WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- Wireless WAN upgradable to 4G or 5G (with antenna ready)
- Quectel EM061K-GL, 4G LTE CAT6, M.2 card, with embedded eSIM functionality
- Quectel EM160R-GL, 4G LTE CAT16, M.2 card, with embedded eSIM functionality
- Quectel RM520N-GL, 5G Sub-6 GHz, M.2 card, with embedded eSIM functionality
- No support

**SIM Card**

- KDDI eSIM Program (Japan)<sup>[4]</sup>
- No physical SIM card inbox

**Ethernet\*\***

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

**NFC<sup>[5]</sup>**

- Near Field Communication
- No support

---

**Notes:**

[1] Wi-Fi® operation (including Wi-Fi® 6, Wi-Fi® 6E, Wi-Fi® 7, etc.) is subject to the regulatory requirements of each country. Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2], [3] Intel® vPro® platform requires the hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. For detailed vPro® support information, please refer to the System Management section.

[4] KDDI eSIM Program has no physical SIM card inbox and is for special bid only.

[5] NFC is NOT available for grey models.

**Ports<sup>[1]</sup>****Standard Ports**

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 2x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 2.1
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)

**Optional Ports\*\*\***

- 1x Nano-SIM card slot (WWAN support models)
- 1x Smart card reader

---

**Notes:**

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

**Docking****Docking**

Various docking solutions supported via Thunderbolt™ / USB-C®.

For more compatible docking solutions, please visit [Docking for ThinkPad® T14 Gen 5 \(Intel®\)](#)

**SECURITY & PRIVACY****Security****ThinkShield**

ThinkShield is a comprehensive security solution that encompasses hardware, software, and supply chain components. For more details, visit [here](#)

**Security Chip**

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

**Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

#### Smart Card Reader

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

#### Fingerprint Reader<sup>[1]</sup>

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

#### BIOS Security

- Certificate-based BIOS authentication
- FIDO (Fast Identity Online) authentication
- NVMe® password
- Power-on password
- Supervisor password
- System management password
- Self-healing BIOS
- More BIOS security features, please visit [BIOS Simulator](#)<sup>[2]</sup>

#### Other Security

- Camera privacy shutter (camera models)
- (Optional) Ultrasonic Human Presence Detection
- (Optional) IR camera for Windows® Hello (facial recognition)
- Privacy Guard with Privacy Alert (models with ThinkPad® Privacy Guard display)

Notes:

[1] Fingerprint reader is standard on grey models and optional on black models.

[2] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

## MANAGEABILITY

### System Management

#### System Management<sup>\*\*</sup><sup>[1]</sup>

- Intel® vPro® Enterprise<sup>[2]</sup>
- Intel® vPro® Essentials
- Non-vPro®

Notes:

[1] Intel® vPro® platform require an eligible Intel® processor, a supported operating system, Intel® LAN and/or WLAN silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. See [Intel® vPro® Platform](#) for details.

[2] Intel® vPro® offers a superset of DASH's defined capabilities.

## SERVICE

### Warranty

#### Base Warranty<sup>\*\*</sup>

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

## ACCESSORIES

### Bundled Accessories

#### Bundled Accessories<sup>\*\*\*</sup><sup>[1]</sup>

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for ThinkPad® T14 Gen 5 \(Intel®\)](#).

## OPERATING REQUIREMENTS

### Operating Environment

#### Temperature<sup>[1]</sup>

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F ) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## ENVIRONMENTAL

### Sustainability

#### Material<sup>[1]</sup>

30% PCC recycled plastic on black top cover  
50% recycled aluminium on grey top cover  
90% recycled magnesium on keyboard frame  
45% PCC recycled plastic on bottom cover of WWAN models  
30% PCC recycled plastic on bottom cover of non-WWAN models  
90% PCC recycled plastic used in speaker enclosure  
90% PCC recycled plastic used in the battery frame  
85% PCC recycled plastic for backlit keycaps  
70% PCC recycled plastic for non-backlit keycaps  
90% PCC recycled plastic used in 65W and 65W slim adapters  
100% plastic free recycled standard packaging

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications<sup>[2]</sup>

- ENERGY STAR® 9.0
- EPEAT™ Gold Registered<sup>[3]</sup>
- ErP Lot 6/26
- RoHS compliant
- TCO Certified, generation 10

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit [epeat.net](https://epeat.net) and [energystar.gov](https://energystar.gov) for more information.

[3] EPEAT™ is registered where applicable, please visit [epeat.net](https://epeat.net) for registration status by country.

## Other Certifications

### Mil-Spec Test

MIL-STD-810H military test passed

### Other Certifications

(Optional) Eyesafe® Certified 2.0

- Feature with \*\* means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with \*\*\* means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

