

iDS-7216HUHI-M2/XT
16-ch 5 MP 1U H.265 AcuSense DVR



- 16 channels and 2 HDD 1U AcuSense DVR
- Support 4-ch Facial Recognition or 16-ch advanced model Perimeter Protection based on Deep Learning algorithm
- Support 16-ch AcuSearch Technology
- Encoding ability up to 4K/8MP @ 8fps; 3K/5MP @12fps
- Up to 32 channels IP camera inputs, each channel up to 8MP
- Up to 24*1080P@30fps decoding ability
- 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP)
- Support All channels Motion Detection Technology
- Support All channels HDTVI Two-Way Audio Technology

▪ Function

Compression and Recording

H.265 Pro+ can be enabled to improve encoding efficiency and reduce data storage costs

Recording at up to 8 MP resolution

Smart Function

Up to 16 channels (analog channel) Motion Detection 2.0

Up to 8 channels (advanced model, analog channel) Perimeter Protection

Up to 4 channels (advanced model, analog channel) human face recognition

Support smart playback to enhance playback efficiency

Network & Ethernet Access

Support Hik-Connect & DDNS (Dynamic Domain Name System)

Output bandwidth limit configurable

▪ Specification

Facial Recognition	
Face Picture Library	Up to 16 face picture libraries; HDD damage will not cause data loss in the face picture library, because the library has been backed up by HDD and flash.
Face Picture Comparison (Captured from Camera)	4-ch face picture comparison alarm (HD analog camera)
Motion Detection 2.0	
Human/Vehicle Analysis	Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights; Quick search by object or event type is supported;
Perimeter Protection	
Human/Vehicle Analysis	Up to 16-ch (advanced model)
Facial Detection	
Facial Detection and Capture	Face picture detection, face picture search ; 4-ch face picture capture
Video and Audio	
IP Video Input	16-ch (up to 32-ch), each up to 8MP
Analog Video Input	16-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDMI Output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz HDMI/VGA simultaneous output
VGA Output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz HDMI/VGA simultaneous output
CVBS Input	PAL/NTSC
CVBS Output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
Synchronous playback	16-ch
HDTVI Input	8 MP(3840 × 2160)@12/15 fps, 3K(2960 × 1665)@25/20 fps, 3K(3328 × 1504)@20fps, 2K(2304 × 1296)@20fps, 5 MP(2560 × 1944)@20 fps, 4 MP(2560 × 1440)@25/30 fps, 1080P@25/30 fps, 720P@25/30fps
AHD Input	5 MP(2560 × 1944)@20 fps, 4 MP(2560 × 1440)@25/30 fps, 1080P@25/30 fps, 720P@25/30fps
HDCVI Input	8 MP(3840 × 2160)@12/15 fps, 3K(2880 × 1620)@20/25 fps, 5 MP(2592 × 1944)@20 fps, 4 MP(2560 × 1440)@25/30 fps, 1080P@25/30 fps, 720P@25/30fps
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Audio Input	1-ch (up to 16-ch is optional), RCA (2.0 Vpp, 1 KΩ), 16-ch via coaxial cable
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the audio input)

Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	8 MP/5 MP/3K/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF
Frame Rate	Main stream: 8 MP@8 fps/3K@12 fps/5 MP@12 fps/4 MP@15 fps/8 MP Lite@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream: WD1/4CIF/CIF@25 fps (P)/30 fps (N)
Video Bitrate	32 Kbps to 10 Mbps
Dual-stream	Support main stream or sub stream
Stream Type	Video, Video & Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Decoding	
Decoding Capability	up to 24-ch 1080P@30fps
Network	
Total Bandwidth	256 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, ISUP
Remote Connection	128
Network Interface	1, RJ45 10/100/1000 Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 12 TB capacity for each disk
Serial Interface	RS-485 (half-duplex)
USB Interface	Front panel: 1 × USB 2.0 Rear panel: 2 × USB 3.0
Alarm In/Out	N/A (optional to support)
General	
Power Supply	12 VDC, 5 A
Consumption	≤ 60 W
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	384 × 317 × 52 mm (15.1 × 12.5 × 2.0 inch)
Weight	≤ 2.1 kg (4.6 lb)

▪ Physical Interface

▪ Available Model

iDS-7216HUHI-M2/XT(STD)

iDS-7216HUHI-M2/XT(STD)/4A+16/4ALM

iDS-7216HUHI-M2/XT(STD)/K+4A+4/1ALM

iDS-7216HUHI-M2/XT(STD)/16A+16/4ALM

iDS-7216HUHI-M2/XT(STD)(B)/4A+16/4ALM

iDS-7216HUHI-M2/XT(STD)(B)/16A+16/4ALM

iDS-7216HUHI-M2/XT(NEU)(B)/4A+16/4ALM

iDS-7216HUHI-M2/XT(NEU)(B)/16A+16/4ALM

iDS-7216HUHI-M2/XT(NEU)

iDS-7216HUHI-M2/XT(NEU)(B)

iDS-7216HUHI-M2/XT(STD)(B)/K16A+16/4ALM

iDS-7216HUHI-M2/XT(STD)(B)/K+4A+4/1ALM

iDS-7216HUHI-M2/XT(STD)/K+16A+16/4ALM

iDS-7216HUHI-M2/XT(STD)/4A/India-L


iDS-7216HUHI-M2/XT(STD)4A/India-L

iDS-7216HUHI-M2/XT(STD)MainBoard/ALG SKD

iDS-7216HUHI-M2/XT(STD)/Chassis/ALG SKD

iDS-7216HUHI-M2/XT(STD)(B)

▪ Dimension



scale/1:1;Unit/mm

See Far, Go Further



www.hikvision.com
support@hikvision.com

